

銅ニッケル抵抗線第五種の抵抗及び重量表

線 径 mm	線径許容差 mm	断面積 mm ²	導体抵抗 Ω/m	導体抵抗許容差 %	重 量 g/m
5.00	± 0.07	19.64	0.002546	± 5%	174.8
4.50	"	15.90	0.003145	"	141.6
4.00	± 0.06	12.57	0.003978	"	111.9
3.50	"	9.621	0.005198	"	85.63
3.20	± 0.05	8.042	0.006218	"	71.58
2.90	"	6.605	0.007572	"	58.78
2.60	"	5.309	0.009419	"	47.25
2.30	"	4.155	0.01203	"	36.98
2.00	± 0.04	3.142	0.01592	"	27.97
1.80	"	2.542	0.01964	"	22.66
1.60	± 0.035	2.011	0.02486	"	17.89
1.50	"	1.767	0.02830	"	15.72
1.40	"	1.539	0.03249	± 6%	13.70
1.30	± 0.030	1.327	0.03768	"	11.81
1.20	"	1.131	0.04421	"	10.07
1.10	"	0.9503	0.05262	"	8.457
1.00	± 0.025	0.7854	0.06366	"	6.990
					g/km
0.90	"	0.6362	0.07859	"	5,662
0.85	"	0.5675	0.08810	"	5,052
0.80	"	0.5027	0.09947	"	4,474
0.75	"	0.4418	0.1132	"	3,931
0.70	± 0.02	0.3848	0.1299	"	3,425
0.65	"	0.3318	0.1508	± 7%	2,952
0.60	"	0.2827	0.1769	"	2,516
0.55	"	0.2376	0.2105	"	2,114
0.50	± 0.015	0.1964	0.2546	"	1,748
0.45	"	0.1590	0.3145	"	1,416
0.40	"	0.1257	0.3978	"	1,119
0.35	"	0.09621	0.5198	± 8%	856.3
0.32	"	0.08042	0.6218	"	715.8
0.29	"	0.06605	0.7572	"	587.8
0.26	± 0.01	0.05309	0.9419	"	472.5
0.23	"	0.04155	1.203	"	369.8
0.20	"	0.03142	1.592	"	279.7
0.18	± 0.009	0.02545	1.964	± 9%	226.6
0.16	± 0.008	0.02011	2.486	"	178.9
0.15	"	0.01767	2.830	"	157.2
0.14	"	0.01539	3.249	"	137.0
0.13	"	0.01327	3.768	"	118.1
0.12	± 0.006	0.01131	4.412	"	100.7
0.11	"	0.009503	5.262	± 10%	84.57
0.10	± 0.003	0.007854	6.366	"	69.90

※ 固有抵抗は $5 \pm 0.75 \mu \Omega \text{cm}$